


# 38B-DB

## ELEMENT CLASS 2

The Tate Solida raised access floor system consists of high-quality floor panels with a highly density chipboard core and a circumferential edge protection banding. A steel sheet is applied to the underside of the panel, which contributes to increasing the load-bearing capacity. In conjunction with an appropriately sized substructure, this raised floor system achieves the technical values described below.




Panels	
Thickness	38.5 mm
Weight per panel	approx. 12 kg
Dimensions	600 mm x 600 mm
Core material	high-density chipboard
Building material class	B2 (core material)
Edge banding	circumferential
Panel face	surface coverings suitable for raised access floors, e.g. homogeneous vinyl, linoleum, HPL, are installed ex works
Panel bottom	Steel sheet

Statics according to EN 12825: 2002	
Ultimate load	> 6 kN
Nominal load	3 kN
Safety factor	2,0
Deflection class	C

Fire protection according to DIN 4102-2: 1977	
Fire-resistance class	Fire retardant supporting structure up to a height of 750 mm

### Substructures

Optional or system-related stringers/cross bars as well as pedestal dimensions of at least M16 or to suit the required installation height



Please scan the QR code or [click here](#) to go to the current product page.



**Tate Global GmbH**  
Zum Stadion 4, 63808 Haibach, Germany  
T: +49 (0) 6021 63949-0 E: [infoDE@tateglobal.com](mailto:infoDE@tateglobal.com) W: [tateglobal.com/de](http://tateglobal.com/de)

© 2025 Tate Global GmbH.  
Tate Global GmbH reserves the right to amend or add to the product specifications without prior notice as part of our commitment to continuous improvements and the observance of legal changes.

tate-solida-38B-DB-datasheet-en-de-v1 6/2025

